

WATER THERMOSTATS TW-2.02 AND TW-2.03

WATER THERMOSTAT TW-2.02

UP TO 100°C



TW-2.02 and tw-2.03 are 8.5 liter stainless steel and plastic bath high accuracy thermostats.

PRODUCT FEATURES

- ▶ High accuracy defined temperature control in the bath.
- ▶ Automatic water level detection for heater protection.
- ▶ External contour and external water volume heating.
- ▶ Intensive water intermixing for accurate temperature maintenance.
- ▶ Easy to disassemble and clean design.

PRODUCT BENEFITS


TW-2.03 is very easy handled, reliable and high performance thermostat for various laboratory needs.

WATER THERMOSTAT TW-2.03

UP TO 90°C



Graph of water temperature gradient in the bath



WATER THERMOSTAT TW-2.03 IS POSSIBLE TO COMBINE WITH MAGNETIC STIRRER MS-01!

WATER THERMOSTATS SPECIFICATIONS

SPECIFICATIONS

		TW - 2.02	TW - 2.03
Temperature range in the bath:	°C	from environmental to 100	from environmental to 90
Accuracy of temperature maintenance in the bath:	°C	±0,1	±0,1
Max time of set temperature achievement:	min	50	50
Max bath capacity	L	8,5	8,5
Temperature stabilization above the environmental	°C	3	3
Water pump productivity for the external contour	L/min	3	3
Voltage and frequency:	V; Hz	220V; 50Hz	220V; 50Hz
Power consumption	kW	up to 1,5	up to 1,5
Size of the device (length x width x height)	mm	320 x 265 x 260	320 x 265 x 260
			2,8